



2-WAY Automated Ball Valves



SERIES	WE01	WE02	WE03	WE04	WE05	WE06	WE07	WE08
Body Type	2-way 2-piece	2-way 3-piece	2-way 3-piece	2-way 2-piece	2-way 3-piece	2-way 3-piece V-ball	2-way 2-piece V-ball	2-way 2-piece
Body Material	316 SS	316 SS	Brass					
Line Sizes	1/2 to 3"	1/2 to 3"	1/2 to 2"	1/2 to 3"	1/2 to 3"	1/2 to 3"	1/2 to 3"	1/2 to 2"
End Connections	Female NPT	Female NPT	Tri-clamp	Flange	Socket weld	Female NPT	Flange	Female NPT

3-WAY Automated Ball Valves



SERIES	WE31	WE33	WE34	WE35
Body Type	3-way	3-way	3-way	3-way
Body Material	316 SS	316 SS	316 SS	Brass
Line Sizes	1/2 to 2"	1/2 to 2"	1/2 to 3"	1/2 to 2"
End Connections	Female NPT	Tri-clamp	Flange	Female NPT



POSITIONERS



SERIES	165 & 265	185 & 285	195 & 295
Body Material	Aluminum or 316 SS	Aluminum or 316 SS	Aluminum
Stroke	0.5 to 6" or 0 to 90°	0.5 to 6" or 0 to 90°	0.19 to 1.38" or 0 to 90°
Air Supply	20 to 101 psig	35 to 116 psi	35 to 116 psi
Enclosure Rating	IP66	NEMA 4X	NEMA 4X

HAND LEVER Ball Valves



SERIES	DBV	BV2	DBVL	SWBV	UBV	MV	SMV2
Body Type	2-way	2-way	2-way	2-way	Uni-flange	2-way	2-way
Body Material	Brass	CF8M	Low lead brass	Brass	Brass	Chrome-plated brass	SS
Line Sizes	1/4 to 3"	1/4 to 3"	1/4 to 3"	1/4 to 3"	1/2 to 1"	1/8 to 1/2"	1/8 to 1/2"
End Connections	Female NPT	Female NPT	Female NPT	Sweat	Female NPT	Female x female NPT or Male x female NPT	Female x female NPT or Male x female NPT



POSITION INDICATORS/ SWITCHES/ TRANSMITTERS



SERIES	QV	Mark 1	Mark 3	UBV	MV	SMV2
Type	Thru-shaft	Magnetic drive	Magnetic drive	Uni-flange	2-way	2-way
Rotation Travel	5 to 360° (switches only)	0 to 340°	1 to 25 revolutions	Brass	Chrome-plated brass	SS
Enclosure Material	Polycarbonate	Aluminum or 316 SS	Aluminum or 316 SS	1/2 to 1"	1/8 to 1/2"	1/8 to 1/2"
Enclosure Rating	NEMA 4, 4X	NEMA 1, 2, 3, 3R, 3S, 4, 4X, 6, 7, 9, 12, & 13	NEMA 1, 2, 3, 3R, 3S, 4, 4X, 6, 7, 9, 12, & 13	Female NPT	Female x female NPT or Male x female NPT	Female x female NPT or Male x female NPT